



ADHESIVE RESINS

兩劑型水性高分子異氰酸酯系接著樹脂

ITEM NO. 製品編號	MAIN COMPONENT 主成分	FORM 外觀	SOLID CONTENT (%) 固型分	VISCOSITY (CPS) 粘度	PH 酸鹼度	MAIN USES 主要用途	SPECIAL FEATURES 特性
AS-500	Isocyanate Ester Polymer 水性高分子異氰酸 酯	White Emulsion 白色乳膠	50 ±2	8,000 ±2000	5~7	Adhesion of Solid Wood Parquets Manufacturing , Artificial Laminate Strip Blocking , Laminate Plank Floor Assembling , Plywood Laminating , Furniture Manufacturing , as well as Wood Work Adhering 大面積實心拼板接著,塊狀積層材接著,平切單板 之貼合,一般家具木工用接著,合板積層之接著	Two Components Adhesive , Add with Crosslinking Agent CA-30 Will Cure at Low Temperature , Excellent Adhesion , Strong Adhesion and Boiling Water Resistant , Environmental Friendly and Contains no Toxic or Harmful Formalin (Formaldehyde) , Phenol , etc. 兩劑型搭配架橋劑 CA-30 具有低溫硬化,接著性能極佳,接 著強度及耐煮沸特性,無污染性,完全不含福馬林,酚等公 害物質