



## RESIN FOR TAPE & LABEL

ITEM NO.	MAIN COMPONENT	FORM	SOLID CONTENT (%)	VISCOSITY (CPS)	MAIN USES	SPECIAL FEATURES	THINNER OR SOLVNET
CS-4120	Acrylic Resin	Transparent Liquid	40±2	3000 ±1000	Two Component for Pressure Sensitive Tape	Neutral Properties, Suitable for Conductive Adhesive tape	Toluene/Ethyl Acetate
CS-4310	Acrylic Resin	Light Yellow Viscous Liquid	40±1	3500 ±1000	One Component for Pressure Sensitive Tape	Good for OPP Tape, Paper Label and PVC Sheet	Toluene/Ethyl Acetate
CS-4310E	Acrylic Resin	Light Yellow Viscous Liquid	40±2	4500±1000	One Component for Pressure Sensitive Tape	Good for PVC Sheet	Toluene/Ethyl Acetate
CS-4312A	Acrylic Resin	Deep Yellow Viscous Liquid	40±2	4000±500	One Component for Pressure Sensitive Tape	Excellent Bonding Strength, Creep Resistance and High Tack	Toluene/Ethyl Acetate
CS-4313	Acrylic Resin	Yellow Viscous Liquid	40±2	3500±1000	One Component for Pressure Sensitive Tape	Good for Label Stocks	Toluene/Ethyl Acetate
CS-4315	Acrylic Resin	Yellow Viscous Liquid	40±1	3500±500	One Component for Pressure Sensitive Tape	Good for Polyester Tape	Toluene/Ethyl Acetate
CS-4515B	Acrylic Resin	Transparent Liquid	40±1	4500±1000	One Component for Pressure Sensitive Tape	Good for Solar Window Film	Toluene/Ethyl Acetate
CS-4313C	Acrylic Resin	Transparent Liquid	30±1	2000±500	Two Component for Pressure Sensitive Tape	Good for Removable Protective Tape	Toluene/Ethyl Acetate
CS-4320	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	40±2	4000±1000	Two Component for Pressure Sensitive Tape	Good for Special Double Side Tape	Toluene/Ethyl Acetate
CS-4520	Vinyl Acetate Acrylic Copolymer	Semitransparent Liquid	45±2	4000±400	Two Component for Pressure Sensitive Tape	Good for Removable Protective Tape	Toluene/Ethyl Acetate
CS-4525	Acrylic Resin	Transparent Liquid	40±1	5000±1000	Two Component for Pressure Sensitive Tape	Excellent Heat Resistant, Good for Heat Resistant Tape	Toluene/Ethyl Acetate
CS-4540	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	40±2	15000±2000	Temporary Adhesion of Fabric Onto Printing Board	Long Retention of Film Surface Tack	Toluene/Ethyl Acetate
CS-4725	Acrylic Resin	Yellow Viscous Liquid	45±2	3500±1000	Two Component for Pressure Sensitive Tape	Good for Special Double Side Tape	Toluene/Ethyl Acetate
CS-4810M	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	50±2	2000±500	One Component for Pressure Sensitive Tape	Good for OPP Tape, Paper Label, PVC Sheet and General Double Side Tape	Toluene/Ethyl Acetate
CS-4811	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	50±2	8000±1000	One Component for Pressure Sensitive Tape	Good for Foam Tape	Toluene/Ethyl Acetate

## RESIN FOR TAPE & LABEL



ITEM NO.	MAIN COMPONENT	FORM	SOLID CONTENT (%)	VISCOSITY (CPS)	MAIN USES	SPECIAL FEATURES	THINNER OR SOLVNET
CS-4816	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	50±2	3000±1000	One Component for Pressure Sensitive Tape	Good for Industrial use Double Side Tape	Toluene/Ethyl Acetate
CS-4820	Vinyl Acetate Acrylic Copolymer	Light Yellow Viscous Liquid	50±2	2000±500	Tow Component for Pressure Sensitive Tape	Good for Double Side Tape	Toluene/Ethyl Acetate
CS-4927	Acrylic Resin	Transparent Liquid	35±1	4000~7000	Tow Component for Pressure Sensitive Tape	Good for Removable Protective Tape	Toluene/Ethyl Acetate



## OTHERS

### 其他

ITEM NO. 製品編號	MAIN COMPONENT 主成分	FORM 外觀	SOLID CONTENT (%) 固型份	VISCOSITY (CPS) 粘度	MAIN USES 主要用途	SPECIAL FEATURES 特性	THINNER OR SOLVNET
CS-10M	Polyvinyl Acetate 醋酸乙稀樹脂	Clear Transparent Viscous Liquid 透明液體	50±2	15000±3000	Adhesive for Polylon to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接著	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接著力強	Methanol 甲醇
CS-10F	Polyvinyl Acetate 醋酸乙稀樹脂 Vinyl Acetate	Clear Transparent Viscous Liquid 透明液體	46±2	5000±1000	Adhesive for Polylon to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接著	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接著力強	Methanol 甲醇
CS-10ML	Polyvinyl Acetate 醋酸乙稀樹脂	Clear Transparent Viscous Liquid 透明液體	40±1	800±200	Adhesive for Polylon to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接著	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接著力強	Methanol 甲醇