



RESIN FOR TAPE & LABEL

膠帶及標籤用樹脂

ITEM NO. 製品編號	MAIN COMPONENT 主成分	FORM 外觀	SOLID CONTENT (%) 固型份	VISCOSITY (CPS) 粘度	MAIN USES 主要用途	SPECIAL FEATURES 特性	THINNER OR SOLVNET
CS-4120	Acrylic Resin 壓克力樹脂	Transparent Liquid 透明液體	40±2	3000 ±1000	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Neutral Properties, Suitable for Conductive Adhesive tape 中性樹脂，適用於導電膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4310	Acrylic Resin 壓克力樹脂	Light Yellow Viscous Liquid 淡黃色液體	40±1	3500 ±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for OPP Tape, Paper Label and PVC Sheet 適用於OPP膠帶，標籤紙及PVC皮	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4310E	Acrylic Resin 壓克力樹脂	Light Yellow Viscous Liquid 淡黃色液體	40±2	4500±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for PVC Sheet 適用於PVC木紋皮	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4312A	Acrylic Resin 壓克力樹脂	Deep Yellow Viscous Liquid 深黃色液體	40±2	4000±500	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Excellent Bonding Strength, Creep Resistance and High Tack 粘著力大，不脫膠，保持力大，初期粘著性高	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4313	Acrylic Resin 壓克力樹脂	Yellow Viscous Liquid 黃色液體	40±2	3500±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for Label Stocks 適用於標籤紙	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4315	Acrylic Resin 壓克力樹脂	Yellow Viscous Liquid 黃色液體	40±1	3500±500	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for Polyester Tape 適用於熱黏立(Polyester)膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4515B	Acrylic Resin 壓克力樹脂	Transparent Liquid 透明液體	40±1	4500±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for Solar Window Film 適用於汽車(玻璃)隔離膜	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4313C	Acrylic Resin 壓克力樹脂	Transparent Liquid 透明液體	30±1	2000±500	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Removable Protective Tape 適用於保護膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4320	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	40±2	4000±1000	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Special Double Side Tape 適用於特殊雙面膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4520	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Semitransparent Liquid 半透明液體	45±2	4000±400	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Removable Protective Tape 適用於保護膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4525	Acrylic Resin 壓克力樹脂	Transparent Liquid 透明液體	40±1	5000±1000	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Excellent Heat Resistant, Good for Heat Resistant Tape 耐熱性佳，適用於耐高溫方面用膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4540	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	40±2	15000±2000	Temporary Adhesion of Fabric Onto Printing Board 襪板糊，織物貼於印花板暫時粘合作用膠	Long Retention of Film Surface Tack 薄膜表面粘性保持久	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4725	Acrylic Resin 壓克力樹脂	Yellow Viscous Liquid 黃色液體	45±2	3500±1000	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Special Double Side Tape 適用於特殊雙面膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4810M	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	50±2	2000±500	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for OPP Tape, Paper Label, PVC Sheet and General Double Side Tape 適用於OPP膠帶，標籤紙，PVC皮及一般雙面膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯
CS-4811	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	50±2	8000±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for f Foam Tape 適用於泡棉膠帶	Toluene/Ethyl Acetate 甲苯/醋酸乙酯



RESIN FOR TAPE & LABEL

膠帶及標籤用樹脂

ITEM NO. 製品編號	MAIN COMPONENT 主成分	FORM 外觀	SOLID CONTENT (%) 固型份	VISCOSITY (CPS) 粘度	MAIN USES 主要用途	SPECIAL FEATURES 特性	THINNER OR SOLVNET
CS-4816	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	50±2	3000±1000	One Component for Pressure Sensitive Tape 一液型感壓性膠帶用膠	Good for Industrial use Double Side Tape 適用於鈔票反用雙面膠帶	Toluene/Ethyl Acetate 甲苯醋酸乙酯
CS-4820	Vinyl Acetate Acrylic Copolymer 醋酸乙烯壓克力共聚樹脂	Light Yellow Viscous Liquid 淡黃色液體	50±2	2000±500	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Double Side Tape 適用於雙面膠帶	Toluene/Ethyl Acetate 甲苯醋酸乙酯
CS-4927	Acrylic Resin 壓克力樹脂	Transparent Liquid 透明液體	35±1	4000~7000	Two Component for Pressure Sensitive Tape 二液型感壓性膠帶用膠	Good for Removable Protective Tape 適用於保護膠帶	Toluene/Ethyl Acetate 甲苯醋酸乙酯



OTHERS

其他

ITEM NO. 製品編號	MAIN COMPONENT 主成分	FORM 外觀	SOLID CONTENT (%) 固型份	VISCOSITY (CPS) 粘度	MAIN USES 主要用途	SPECIAL FEATURES 特性	THINNER OR SOLVNET
CS-10M	Polyvinyl Acetate 醋酸乙稀樹脂	Clear Transparent Viscous Liquid 透明液體	50±2	15000±3000	Adhesive for Polyton to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接着	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接着力強	Methanol 甲醇
CS-10F	Polyvinyl Acetate 醋酸乙稀樹脂 Vinyl Acetate	Clear Transparent Viscous Liquid 透明液體	46±2	5000±1000	Adhesive for Polyton to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接着	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接着力強	Methanol 甲醇
CS-10ML	Polyvinyl Acetate 醋酸乙稀樹脂	Clear Transparent Viscous Liquid 透明液體	40±1	800±200	Adhesive for Polyton to Wood, Metal, Plastic, Cement, Paper, Cloth, Glass Fiber, Etc. 保麗龍與木材、金屬、塑膠、水泥、紙、布料、玻璃纖維等之接着	Fast Drying Speed, Strong Bonding Strength 乾燥速度快, 接着力強	Methanol 甲醇